



Main

| | |
|---------------------------|----------------------------------|
| Range of product | Thorsman |
| Product or component type | Wall plug |
| Device short name | TP |
| Provided equipment | Without screw |
| Device application | Lightweight installation |
| Drilling diameter | 5.5 mm brick 5.5 mm concrete |
| Drilling depth | >= 20 mm |
| Screw diameter | 3.5...5 mm |
| Material | PEHD (polyethylene high density) |

Complementary

| | |
|---------------------------------------|--|
| Practical load capacity | 0.3 kN shear solid brick 4.5 0.4 kN shear concrete C25 4.5 0.15 kN pull-out load concrete C25 6 0.15 kN pull-out load solid brick 6 |
| Practical load capacity | 40 kg shear concrete 4.5 15 kg pull-out load concrete 6 30 kg shear solid brick 4.5 15 kg pull-out load solid brick 6 |
| Colour tint | White |
| Ambient air temperature for operation | -50...80 °C |
| Diameter | 5.5 mm |
| Length | 16.5 mm |

Environment

| | |
|-------------------------------|------------|
| Quantity per set | Set of 500 |
| Sale per indivisible quantity | 1 |
| Product weight | 0.00023 kg |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

1000017