



### Main

Range of product	Thorsman
Product or component type	Wall plug
Device short name	TP
Provided equipment	Without screw
Device application	Lightweight installation
Drilling diameter	5.5 mm brick 5.5 mm concrete 5 mm ALC concrete
Drilling depth	>= 40 mm
Screw diameter	3.5...5 mm
Material	PEHD (polyethylene high density)

### Complementary

Practical load capacity	0.04 kN pull-out load low density concrete 500 and expanded clay 6 0.6 kN shear concrete C25 4.5 0.4 kN pull-out load concrete C25 6 0.5 kN shear solid brick 4.5 0.3 kN pull-out load solid brick 6 0.15 kN shear low density concrete 500 and expanded clay 4.5
Practical load capacity	60 kg shear concrete C25 4.5 4 kg pull-out load low density concrete 500 and expanded clay 6 40 kg pull-out load concrete C25 6 50 kg shear solid brick 4.5 30 kg pull-out load solid brick 6 15 kg shear low density concrete 500 and expanded clay 4.5
Colour tint	Red
Ambient air temperature for operation	-50...80 °C
Diameter	5.5 mm
Length	35 mm

### Environment

Quantity per set	Set of 20000
Sale per indivisible quantity	1
Type of packing	Bag

---

Product weight	0.0005 kg
----------------	-----------

---

### Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---