



Main

Range of product	Thorsman
Product or component type	Wall plug
Device short name	TP
Provided equipment	Without screw
Device application	Lightweight installation
Drilling diameter	8 mm brick 8 mm concrete 7 mm ALC concrete
Drilling depth	>= 45 mm
Screw diameter	5...6 mm
Material	PEHD (polyethylene high density)

Complementary

Practical load capacity	1.2 kN shear concrete C25 4.5 0.8 kN pull-out load concrete C25 6 0.7 kN shear solid brick 4.5 0.4 kN pull-out load solid brick 6 0.25 kN shear low density concrete 500 and expanded clay 4.5 0.1 kN pull-out load low density concrete 500 and expanded clay 6
Practical load capacity	25 kg shear low density concrete 500 and expanded clay 4.5 120 kg shear concrete C25 4.5 80 kg pull-out load concrete C25 6 70 kg shear solid brick 4.5 40 kg pull-out load solid brick 6 10 kg pull-out load low density concrete 500 and expanded clay 6
Colour tint	Brown
Ambient air temperature for operation	-50...80 °C
Diameter	8 mm
Length	40 mm

Environment

Quantity per set	Set of 100
Sale per indivisible quantity	1
Product weight	0.00128 kg

Contractual warranty

Warranty period	18 months
-----------------	-----------
