



### Main

Range of product	Kaedra
Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for modular device
Accessories included with enclosure	3 wiring straps 3 marking kits

### Complementary

Enclosure mounting	Surface
9 mm pitches	24
Number of 18 mm modules per row	12
Total number of 18 mm modules	36
Number of horizontal rows	3
Electrical insulation class	Class II Double insulation
Provided equipment	3 marking kit 3 wiring strap
Type of front cover	Transparent Reversible
Power dissipation in W	46 W
[In] rated current	90 A
Type of rail	DIN
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Width	340 mm
Height	610 mm
Depth	160 mm
Colour	Door : transparent green Enclosure : light grey ( RAL 7035 )

Targeted country	Italy
<b>Environment</b>	
Standards	EN 50102 IEC 60529 IEC 60439-3 IEC 670 IEC 60695-2-1
Fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C
<b>Offer Sustainability</b>	
Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0622 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations
<b>Contractual warranty</b>	
Warranty period	18 months