



Main

| | |
|-------------------------------------|---|
| Range of product | Kaedra |
| Range | Kaedra |
| Product or component type | Weatherproof enclosure |
| Enclosure type | Enclosure for modular device with interface |
| Accessories included with enclosure | 1 marking kit 1 plate for push-button controls 1 wiring strap |

Complementary

| | |
|---------------------------------|--|
| Enclosure mounting | Surface |
| 9 mm pitches | 24 |
| Number of 18 mm modules per row | 12 |
| Total number of 18 mm modules | 12 |
| Number of horizontal rows | 1 |
| Electrical insulation class | Class II Double insulation |
| Number of openings of interface | 1 |
| Number of plates | 1 for push-button controls |
| Provided equipment | 1 marking kit 1 wiring strap 1 plate for push-button control |
| Type of front cover | Reversible Transparent |
| Power dissipation in W | 28 W |
| [In] rated current | 90 A |
| Type of rail | DIN |
| Locking options description | Optional keylock |
| Enclosure material | Self-extinguishing polymer |
| Base dimension | 90 x 100 mm |

| | |
|------------------|---|
| Width | 448 mm |
| Height | 280 mm |
| Depth | 160 mm |
| Colour | Door : transparent green Enclosure : light grey (RAL 7035) |
| Targeted country | Italy |

Environment

| | |
|---------------------------------------|--|
| Standards | IEC 60439-3 IEC 670 IEC 60529 IEC 60695-2-1 EN 50102 |
| Fire resistance | 650 °C conforming to IEC 60695-2-1 |
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK09 conforming to EN 50102 |
| Environmental characteristic | UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013 |
| Overvoltage category | II |
| Ambient air temperature for operation | -25...60 °C |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0622 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available Product environmental |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|