



### Main

Range of product	Kaedra
Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for plug and socket
Accessories included with enclosure	1 plate for 65 x 85 power outlets 4 plates for push-button controls

### Complementary

Enclosure mounting	Surface
9 mm pitches	10
Number of 18 mm modules per row	5
Total number of 18 mm modules	5
Number of horizontal rows	1
Electrical insulation class	Class II Double insulation
Number of openings of interface	4
Number of plates	4 for push-button controls 1 for 65 x 85 power outlets
Provided equipment	1 plate for 65 x 85 power outlet 4 plate for push-button control
Type of front cover	Opaque
[In] rated current	63 A
Type of rail	DIN
Enclosure material	Self-extinguishing polymer
Base dimension	90 x 100 mm
Width	138 mm
Height	610 mm
Depth	160 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Colour	Enclosure : light grey ( RAL 7035 )
Targeted country	Italy

## Environment

Standards	IEC 60529 EN 50102 IEC 670 IEC 60439-3 IEC 60695-2-1
Fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0622 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------