



### Main

|                                     |                                                                                    |
|-------------------------------------|------------------------------------------------------------------------------------|
| Range of product                    | Kaedra                                                                             |
| Range                               | Kaedra                                                                             |
| Product or component type           | Weatherproof enclosure                                                             |
| Enclosure type                      | Enclosure for plug and socket                                                      |
| Accessories included with enclosure | 2 plates for 65 x 85 power outlets<br>1 plate for 65 x 65 or 75 x 75 power outlets |

### Complementary

|                                 |                                                                                 |
|---------------------------------|---------------------------------------------------------------------------------|
| Enclosure mounting              | Surface                                                                         |
| 9 mm pitches                    | 10                                                                              |
| Number of 18 mm modules per row | 5                                                                               |
| Total number of 18 mm modules   | 5                                                                               |
| Number of horizontal rows       | 1                                                                               |
| Electrical insulation class     | Double insulation<br>Class II                                                   |
| Number of openings of interface | 2                                                                               |
| Number of plates                | 1 for 65 x 65 or 75 x 75 power outlets<br>2 for 65 x 85 power outlets           |
| Provided equipment              | 1 plate for 65 x 65 or 75 x 75 power outlet<br>2 plate for 65 x 85 power outlet |
| Type of front cover             | Transparent                                                                     |
| Power dissipation in W          | 12 W                                                                            |
| [In] rated current              | 63 A                                                                            |
| Type of rail                    | DIN                                                                             |
| Locking options description     | Optional keylock                                                                |
| Enclosure material              | Self-extinguishing polymer                                                      |
| Base dimension                  | 90 x 100 mm                                                                     |
| Width                           | 138 mm                                                                          |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

|                  |                                                                 |
|------------------|-----------------------------------------------------------------|
| Height           | 460 mm                                                          |
| Depth            | 160 mm                                                          |
| Colour           | Door : transparent green<br>Enclosure : light grey ( RAL 7035 ) |
| Targeted country | Italy                                                           |

## Environment

|                                       |                                                                                                                |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Standards                             | IEC 670<br>IEC 60695-2-1<br>IEC 60529<br>EN 50102<br>IEC 60439-3                                               |
| Fire resistance                       | 650 °C conforming to IEC 60695-2-1                                                                             |
| IP degree of protection               | IP65 conforming to IEC 60529                                                                                   |
| IK degree of protection               | IK09 conforming to EN 50102                                                                                    |
| Environmental characteristic          | UV resistant class 3 conforming to ISO 4582 2010<br>Ultraviolet degradation test conforming to ISO 4892-2 2013 |
| Overvoltage category                  | II                                                                                                             |
| Ambient air temperature for operation | -25...60 °C                                                                                                    |

## Offer Sustainability

|                                  |                                                                                                                                       |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status         | Green Premium product                                                                                                                 |
| RoHS (date code: YYWW)           | Compliant - since 0622 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product environmental profile    | Available                                                                                                                             |
| Product end of life instructions | Need no specific recycling operations                                                                                                 |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|