



### Main

|                                     |  |
|-------------------------------------|--|
| Range of product                    | Kaedra   |
| Range                               | Kaedra   |
| Product or component type           | Weatherproof enclosure   |
| Enclosure type                      | Enclosure for plug and socket  |
| Accessories included with enclosure | 6 plates for 65 x 85 power outlets<br>2 plates for 65 x 65 or 75 x 75 power outlets<br>2 wiring straps |

### Complementary

|                                 |   |
|---------------------------------|---|
| Enclosure mounting              | Surface   |
| 9 mm pitches                    | 24  |
| Number of 18 mm modules per row | 12  |
| Total number of 18 mm modules   | 12  |
| Number of horizontal rows       | 1   |
| Electrical insulation class     | Double insulation<br>Class II   |
| Number of openings of interface | 6   |
| Number of plates                | 2 for 65 x 65 or 75 x 75 power outlets<br>6 for 65 x 85 power outlets                             |
| Provided equipment              | 2 wiring strap<br>2 plate for 65 x 65 or 75 x 75 power outlet<br>6 plate for 65 x 85 power outlet |
| Type of front cover             | Transparent   |
| Power dissipation in W          | 23 W  |
| [In] rated current              | 63 A  |
| Type of rail                    | DIN   |
| Locking options description     | Optional keylock  |
| Enclosure material              | Self-extinguishing polymer  |
| Base dimension                  | 90 x 100 mm   |

|                  |   |
|------------------|---|
| Width            | 340 mm  |
| Height           | 460 mm  |
| Depth            | 160 mm  |
| Colour           | Door : transparent green<br>Enclosure : light grey ( RAL 7035 ) |
| Targeted country | Italy   |

## Environment

|                                       |  |
|---------------------------------------|--|
| Standards                             | IEC 60529<br>IEC 60439-3<br>IEC 60695-2-1<br>IEC 670<br>EN 50102   |
| Fire resistance                       | 650 °C conforming to IEC 60695-2-1   |
| IP degree of protection               | IP65 conforming to IEC 60529   |
| IK degree of protection               | IK09 conforming to EN 50102  |
| Environmental characteristic          | UV resistant class 3 conforming to ISO 4582 2010<br>Ultraviolet degradation test conforming to ISO 4892-2 2013 |
| Overtoltage category                  | II   |
| Ambient air temperature for operation | -25...60 °C  |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 0622 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product environmental profile    | Available<br><a href="#">Product environmental</a>  |
| Product end of life instructions | Need no specific recycling operations   |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|