



### Main

Range of product	Kaedra
Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for plug and socket
Accessories included with enclosure	2 wiring straps 1 plate for 65 x 65 or 75 x 75 power outlets

### Complementary

Enclosure mounting	Surface
9 mm pitches	16
Number of 18 mm modules per row	8
Total number of 18 mm modules	8
Number of horizontal rows	1
Electrical insulation class	Double insulation Class II
Number of openings of interface	2
Number of plates	1 for 65 x 65 or 75 x 75 power outlets
Provided equipment	2 wiring strap 1 plate for 65 x 65 or 75 x 75 power outlet
Type of front cover	Transparent
Power dissipation in W	15 W
[In] rated current	63 A
Type of rail	DIN
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Base dimension	103 x 225 mm
Width	236 mm
Height	460 mm

Depth	160 mm
Colour	Door : transparent green Enclosure : light grey ( RAL 7035 )
Targeted country	Italy

## Environment

Standards	IEC 670 EN 50102 IEC 60439-3 IEC 60529 IEC 60695-2-1
Fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0622 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------