

Product data sheet

Characteristics

1051007

Thorsman - TPN-6x35 - universal fixing - with 50 mm screw - set of 25



Main

| | |
|---------------------------|------------------|
| Range of product | Thorsman |
| Product or component type | Universal fixing |
| Device short name | TPN |
| Provided equipment | Screw |
| Drilling diameter | 6 mm |
| Drilling depth | >= 50 mm |
| Screw diameter | 4 mm |
| Screw length | 50 mm |

Complementary

| | |
|---------------------------------------|---|
| Colour tint | Grey |
| Material | PA (polyamide) plug Hardened steel bright galvanized screw |
| Practical load capacity | 500 N shear concrete C25 4.5 100 N pull-out load concrete C25 6 200 N shear low density concrete 500 and expanded clay 4.5 60 N pull-out load low density concrete 500 and expanded clay 6 180 N shear 13 mm plasterboard 4.5 60 N pull-out load 13 mm plasterboard 6 260 N shear 2 x 13 mm plasterboard 4.5 80 N pull-out load 2 x 13 mm plasterboard 6 |
| Thickness | 0...16 mm fixture 9 mm board maximum |
| Ambient air temperature for operation | -20...80 °C |
| Diameter | 6 mm |
| Length | 35 mm |

Environment

| | |
|------------------|-----------|
| Quantity per set | Set of 25 |
| Product weight | 0.0045 kg |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

1051007