



### Main

Range	Acti 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	3L + N
Total number of 18 mm modules	12

### Complementary

Number of ways	Incomer : 1 way N + 3 L Outgoer : 8 ways N + L
Poles configuration for 1 way	Incomer : 1 x 4P Outgoer : 1 x 1P + N Incomer : 1 x 3P + N Outgoer : 1 x 2P
Connection pitch	Incomer : 18 mm Outgoer : 9 mm
Connector type	Tooth
Distance between way	Incomer : 72 mm Outgoer : 18 mm
Marking	Outgoer : N L1 N L2 N L3 Incomer : N L1 L2 L3
Incomer device	ID on the left
Insulation	Insulated
Device presentation	Uncuttable
[Ie] rated operational current	80 A ( 40 °C )
[Ue] rated operational voltage	400 V AC Ph/Ph 230 V AC Ph/N
[Ui] rated insulation voltage	440 V AC conforming to IEC 61439-1
[Uimp] rated impulse withstand voltage	6 kV
Mounting mode	Horizontal
Mounting location	Top on tunnel type terminals
9 mm pitches	24
Width	216 mm
Colour	Light grey ( RAL 7035 )
Range compatibility	Acti 9 iDPN Vigi

Acti 9 iDPN  
Acti 9 C40  
Acti 9 DT40  
Acti 9 DT60  
Acti 9 iDPN N Arc  
Acti 9 iARC DPNN

---

## Environment

---

Standards	IEC 60947-7 EN/IEC 60439-1
Fire resistance	960 °C ( 30 s ) conforming to IEC 60695-2-1
Pollution degree	3

---

## Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---