



### Main

Range of product	Pragma UP
Range	Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Width	330 mm embedded 344 mm outside
Height	710 mm embedded 749 mm outside
Depth	13.4 mm outside 90 mm embedded
Number of 18 mm modules per row	12
Number of horizontal rows	4
Provided equipment	Terminal block ( 2 ) Identification label ( 1 )
Type of front cover	Adjustable Reversible Opaque

### Complementary

Enclosure mounting	Flush
9 mm pitches	24
Total number of 18 mm modules	48
[In] rated current	63 A
[Ui] rated insulation voltage	< 690 V
Type of rail	DIN
Cable entry	Flexible flaps
Number of terminal blocks	2 neutral / earth terminal block with 24 screw connection outgoers
Distribution block outgoers	12 x 25 mm <sup>2</sup> for neutral / earth 36 x 4 mm <sup>2</sup> for neutral / earth
Locking options description	Optional keylock
Enclosure material	Door : electrolytic galvanised steel Enclosure : self-extinguishing plastic
Colour	Door : white ( RAL 9016 ) Enclosure : white ( RAL 9016 )

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

---

Market segment	Small commercial Residential
----------------	---------------------------------

---

## Environment


---

Fire resistance	Enclosure : 650 °C conforming to IEC 60695-2-1
Overvoltage category	II
Ambient air temperature for operation	-20...40 °C
Standards	IEC 60439-3 DIN 43871 IEC 60695-2-1

---

## Offer Sustainability

---

RoHS (date code: YYWW)	Compliant - since 0626 - Schneider Electric declaration of conformity <a href="#"> Schneider Electric declaration of conformity</a>
------------------------	---

---

## Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---