

# Product data sheet

## Characteristics

# 1220010

## Thorsman - TPD-VS - cavity fixing - without screw - set of 100



### Main

|                           |   |
|---------------------------|---|
| Range of product          | Thorsman                                      |
| Product or component type | Cavity fixing                                 |
| Device short name         | TPD-VS  |
| Provided equipment        | Without screw                                 |
| Device application        | 9 mm lightweight installation in plasterboard |
| Colour tint               | White   |
| Quantity per set          | Set of 100                                    |

### Complementary

|                         |   |
|-------------------------|---|
| Mounting support        | Wall mounted  |
| Material                | Glass fibre reinforced<br>PA (polyamide)                          |
| Practical load capacity | 0.5 kN pull-out load : 13 mm board<br>0.19 kN shear : 13 mm board |
| Thickness               | 0...12 mm fixture   |
| Diameter                | 13 mm   |
| Length                  | 37 mm   |
| Product weight          | 0.177 kg  |

### Environment

|                                       |             |
|---------------------------------------|-------------|
| Ambient air temperature for operation | -40...80 °C |
|---------------------------------------|-------------|

### Offer Sustainability

|                        |   |
|------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 1002 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                  | Reference not containing SVHC above the threshold<br>Reference not containing SVHC above the threshold                                |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|