

Product: 836-A2AC

Description: 836 Pressure Controls - General Industrial



Representative Photo
Only (actual product
may vary based on
configuration
selections)

Note

Modified Industrial Control Options are Available. Email to RADBQUOTE@RA.ROCKWELL.COM

-See "OPTIONS" Section Below:
 -LED option
 -Custom Factory Installed Modification text field

PRESSURE CONTROLS

Device Style	Device Style A, Internal Copper Alloy Bellows
Custom Trip or Reset Setting	Customer Specified Setting
Pressure Specifications	6 ...140 psi.
Adjustable Differential psi (Approximate Mid-Range Values)	3...35
Maximum Line Pressure	280

ENCLOSURE

Enclosure Type	Type 1 Enclosure
----------------	------------------

MODIFICATIONS

Factory Modifications	No Modifications
-----------------------	------------------

MODIFIED INDUSTRIAL CONTROL OPTIONS

LED option	No LED pilot option
------------	---------------------

NOTES

Note===>	Standard contact block - Single-pole, double-throw, snap action. Non-inductive ratings, 5 A, 240V. 3 A, 600V. Control circuit ratings AC - 125 VA, 24...600V. DC - 57.5 VA, 115...230V.
----------	---

CERTIFICATIONS AND APPROVALS

To check whether product has certifications that are not listed below, see: <http://www.rockwellautomation.com/global/certification/overview.page>

CCC Certificate

2017010305951970

Allen-Bradley 836-A2AC