



Main

| | |
|---------------------------|--------------------------|
| Range of product | Thorsman |
| Product or component type | Cavity fixing |
| Device short name | TSP |
| Provided equipment | Screw |
| Mounting support | Board material 3...40 mm |
| Device application | Board material 3...40 mm |
| Mounting support | Wall mounted |
| Thread type | M5 |
| Screw diameter | 5 mm |
| Screw length | 75 mm |
| Drilling diameter | 10 mm |
| Colour tint | Blue/White |

Complementary

| | |
|------------------|------------|
| Quantity per set | Set of 25 |
| Product weight | 0.00196 kg |

Environment

| | |
|---------------------------------------|---|
| Material | PA (polyamide) collar Steel electroplated screw PA (polyamide) spring |
| Practical load capacity | 250 N shear 13 mm board 4.5 75 N pull-out load 13 mm board 6 400 N shear 2 x 13 mm board 4.5 150 N pull-out load 2 x 13 mm board 6 |
| Thickness | 0...37 mm fixture 13 mm board 0...24 mm fixture 2 x 13 mm board |
| Environmental characteristic | Corrosion resistance |
| Ambient air temperature for operation | -40...80 °C |
| Diameter | 20 mm |
| Length | 77 mm |

1249002

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
