



### Main

Range of product	Kaedra
Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for plug and socket
Accessories included with enclosure	1 plate for push-button controls 1 terminal block 4 holes 2 plates for 65 x 85 power outlets

### Complementary

Enclosure mounting	Surface
9 mm pitches	10
Number of 18 mm modules per row	5
Total number of 18 mm modules	5
Number of horizontal rows	1
Electrical insulation class	Class II Double insulation
Number of openings of interface	2
Number of plates	1 for push-button controls 2 for 65 x 85 power outlets
Provided equipment	1 plate for push-button control 2 plate for 65 x 85 power outlet 1 terminal block 4 holes
Type of front cover	Transparent
Power dissipation in W	12 W
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	3
Number of terminal blocks	1 with 4 outgoers
Distribution block outgoers	2 x 10 mm <sup>2</sup> 2 x 16 mm <sup>2</sup>
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Base dimension	90 x 100 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Width	138 mm
Height	460 mm
Depth	160 mm
Colour	Door : transparent green Enclosure : light grey ( RAL 7035 )
Targeted country	France

## Environment

Standards	EN 50102 EN 50262 IEC 60439-3 IEC 60529 IEC 670
Fire resistance	750 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

## Contractual warranty

Warranty period	18 months
-----------------	-----------