



Main

Range of product	Kaedra
Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for plug and socket
Accessories included with enclosure	2 wiring straps 1 terminal block 8 holes 1 terminal block support 4 plates for 65 x 85 power outlets 1 plate for push-button controls

Complementary

Enclosure mounting	Surface
9 mm pitches	16
Number of 18 mm modules per row	8
Total number of 18 mm modules	8
Number of horizontal rows	1
Electrical insulation class	Class II Double insulation
Number of openings of interface	4
Number of plates	1 for push-button controls 4 for 65 x 85 power outlets
Provided equipment	2 wiring strap 1 plate for push-button control 4 plate for 65 x 85 power outlet 1 terminal block 8 holes 1 terminal block support
Type of front cover	Transparent
Power dissipation in W	15 W
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	7
Number of terminal blocks	1 with 8 outgoers
Distribution block outgoers	4 x 10 mm ² 4 x 16 mm ²

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Base dimension	90 x 100 mm
Width	236 mm
Height	460 mm
Depth	160 mm
Colour	Door : transparent green Enclosure : light grey (RAL 7035)
Targeted country	France

Environment

Standards	IEC 670 IEC 60529 EN 50262 IEC 60439-3 EN 50102
Fire resistance	750 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------