

Product data sheet

Characteristics

13165

Kaedra - versatile for power outlet - 1 x 8 modules - 236 x 460 mm



Main

| | |
|---------------------------|--------------------------------------|
| Range of product | Kaedra |
| Range | Kaedra |
| Product or component type | Weatherproof enclosure |
| Enclosure type | Versatile enclosure for power outlet |

Complementary

| | |
|---------------------------------|-----------------------------------------------------------------|
| Enclosure mounting | Surface |
| 9 mm pitches | 16 |
| Number of 18 mm modules per row | 8 |
| Total number of 18 mm modules | 8 |
| Number of horizontal rows | 1 |
| Electrical insulation class | Class II Double insulation |
| Type of front cover | Transparent |
| Power dissipation in W | 15 W |
| [In] rated current | 63 A |
| Type of rail | DIN |
| Number of pre-cutouts PG ISO | 7 |
| Locking options description | Optional keylock |
| Enclosure material | Self-extinguishing polymer |
| Width | 236 mm |
| Height | 460 mm |
| Depth | 160 mm |
| Colour | Door : transparent green Enclosure : light grey (RAL 7035) |
| Targeted country | France |

Environment

| | |
|-----------|-------------------------------------------------------------|
| Standards | EN 50102 EN 50262 IEC 60439-3 IEC 60529 IEC 670 |
|-----------|-------------------------------------------------------------|

| | |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Fire resistance | 750 °C conforming to IEC 60695-2-1 |
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK09 conforming to EN 50102 |
| Environmental characteristic | UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013 |
| Overvoltage category | II |
| Ambient air temperature for operation | -25...60 °C |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|