



### Main

Range of product	Kaedra
Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for power outlet
Accessories included with enclosure	1 plate for 50 x 50 power outlets

### Complementary

Enclosure mounting	Surface
9 mm pitches	8
Number of 18 mm modules per row	4
Total number of 18 mm modules	4
Number of horizontal rows	1
Electrical insulation class	Class II Double insulation
Number of openings of interface	3
Number of plates	1 for 50 x 50 power outlets
Provided equipment	1 plate for 50 x 50 power outlet
Type of front cover	Transparent
Power dissipation in W	10 W
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	1
Number of terminal blocks	1 with 4 outgoers
Distribution block outgoers	2 x 10 mm <sup>2</sup> 2 x 16 mm <sup>2</sup>
Locking options description	Optional keylock
Enclosure material	Housing : self-extinguishing polymer
Product weight	0.61 kg
Base dimension	65 x 85 mm
Width	98 mm
Height	392 mm
Depth	98 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Colour	Door : transparent green Enclosure : light grey ( RAL 7035 )
Market segment	Small commercial Residential

## Environment

Standards	IEC 60695-2-1 EN 62262 IEC 60529 IEC 60439-3 IEC 670 EN 50262
Fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
Overvoltage category	II
Ambient air temperature for operation	-25...40 °C

## Contractual warranty

Warranty period	18 months
-----------------	-----------