



Main

Range of product	Kaedra
Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for power outlet
Accessories included with enclosure	2 plates for push-button controls 2 wiring straps 8 plates for 65 x 85 power outlets

Complementary

Enclosure mounting	Surface
9 mm pitches	36
Number of 18 mm modules per row	18
Total number of 18 mm modules	19
Number of horizontal rows	1
Electrical insulation class	Class II Double insulation
Number of openings of interface	8
Number of plates	2 for push-button controls 8 for 65 x 85 power outlets
Provided equipment	2 wiring strap 8 plate for 65 x 85 power outlet 2 plate for push-button control
Type of front cover	Transparent
Power dissipation in W	39 W
[In] rated current	90 A
Type of rail	DIN
Number of pre-cutouts PG ISO	17
Number of terminal blocks	1 with 16 outgoers
Locking options description	Optional keylock
Enclosure material	Housing : self-extinguishing polymer
Product weight	3.4 kg
Base dimension	90 x 100 mm
Width	448 mm

Height	460 mm
Depth	160 mm
Colour	Door : transparent green Enclosure : light grey (RAL 7035)
Market segment	Residential Small commercial

Environment

Standards	EN 50262 EN 62262 IEC 60439-3 IEC 60529 IEC 60695-2-1 IEC 670
Fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
Overvoltage category	II
Ambient air temperature for operation	-25...40 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------