



Main

Range of product	Kaedra
Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for power outlet
Accessories included with enclosure	1 terminal block 4 holes

Complementary

Enclosure mounting	Surface
9 mm pitches	10
Number of 18 mm modules per row	5
Total number of 18 mm modules	5
Number of horizontal rows	1
Electrical insulation class	Double insulation Class II
Number of openings of interface	1
Provided equipment	1 terminal block 4 holes
Type of front cover	Transparent
Power dissipation in W	12 W
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	3
Number of terminal blocks	1 with 4 outgoers
Distribution block outgoers	2 x 10 mm ² 2 x 16 mm ²
Locking options description	Optional keylock
Enclosure material	Housing : self-extinguishing polymer
Product weight	1.2 kg
Base dimension	103 x 225 mm
Width	138 mm
Height	460 mm
Depth	160 mm
Colour	Door : transparent green

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Enclosure : light grey (RAL 7035)

Market segment	Small commercial Residential
----------------	---------------------------------

Environment

Standards	EN 50262 IEC 670 IEC 60439-3 IEC 60695-2-1 IEC 60529 EN 62262
Fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
Overvoltage category	II
Ambient air temperature for operation	-25...40 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------
