

Product data sheet

Characteristics

13187

Kaedra - for power outlet - 3 openings - 1 x 12 modules - 340 x 460 mm



Main

Range of product	Kaedra
Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for power outlet
Accessories included with enclosure	1 plate for 65 x 65 or 75 x 75 power outlets 2 wiring straps

Complementary

Enclosure mounting	Surface
9 mm pitches	24
Number of 18 mm modules per row	12
Total number of 18 mm modules	12
Number of horizontal rows	1
Electrical insulation class	Class II Double insulation
Number of openings of interface	3
Number of plates	1 for 65 x 65 or 75 x 75 power outlets
Provided equipment	2 wiring strap 1 plate for 65 x 65 or 75 x 75 power outlet
Type of front cover	Transparent
Power dissipation in W	28 W
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	17
Number of terminal blocks	1 with 8 outgoers
Distribution block outgoers	4 x 10 mm ² 4 x 16 mm ²
Locking options description	Optional keylock
Enclosure material	Housing : self-extinguishing polymer
Product weight	2.7 kg
Base dimension	103 x 225 mm
Width	340 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Height	460 mm
Depth	160 mm
Colour	Door : transparent green Enclosure : light grey (RAL 7035)
Market segment	Small commercial Residential

Environment

Standards	IEC 60695-2-1 IEC 60529 IEC 670 EN 50262 IEC 60439-3 EN 62262
Fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
Overvoltage category	II
Ambient air temperature for operation	-25...40 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------