

Product data sheet

Characteristics

13192

Kaedra - versatile for power outlet - 1 x 12+1
modules - 340 x 460mm



Main

Range of product	Kaedra
Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Versatile enclosure for power outlet

Complementary

Enclosure mounting	Surface
9 mm pitches	24
Number of 18 mm modules per row	12
Total number of 18 mm modules	12
Number of horizontal rows	1
Electrical insulation class	Double insulation Class II
Type of front cover	Transparent
Power dissipation in W	28 W
[In] rated current	90 A
Type of rail	DIN
Number of pre-cutouts PG ISO	17
Locking options description	Optional keylock
Enclosure material	Housing : self-extinguishing polymer
Product weight	2.8 kg
Width	340 mm
Height	460 mm
Depth	160 mm
Colour	Door : transparent green Enclosure : light grey (RAL 7035)
Market segment	Small commercial Residential

Environment

Standards	EN 50262 IEC 60529
-----------	-----------------------

13192

IEC 60439-3
IEC 60695-2-1
IEC 670
EN 62262

Fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
Overvoltage category	II
Ambient air temperature for operation	-25...40 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------