



### Main

Range	Mini Pragma
Range of product	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	12
Number of horizontal rows	1
Provided equipment	Marking kit ( 1 ) Terminal block support ( 1 ) Terminal block 8 holes ( 1 ) Flush mounting kit ( 1 )
Type of front cover	Transparent

### Complementary

Enclosure mounting	Flush
9 mm pitches	24
Total number of 18 mm modules	12
[In] rated current	63 A
Number of terminal blocks	1 8 Quick outgoers
Distribution block outgoers	4 x 10 mm <sup>2</sup> 4 x 16 mm <sup>2</sup>
Locking options description	Keylock option
Enclosure material	Enclosure : self-extinguishing material
Colour	Enclosure : white ( RAL 9003 )

### Environment

Standards	EN 50102 IEC 60695-2-1 EN 60439-3 IEC 60529 IEC 60439-3
Fire resistance	Back part : 850 °C conforming to IEC 60695-2-1 Front face : 750 °C conforming to IEC 60695-2-1
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102

Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---