



### Main

Range	Mini Pragma
Range of product	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	12
Number of horizontal rows	1
Provided equipment	Marking kit ( 1 ) Insulating plug ( 1 )
Type of front cover	Transparent

### Complementary

Enclosure mounting	Surface
9 mm pitches	24
Total number of 18 mm modules	12
[In] rated current	63 A
Type of rail	DIN
Locking options description	Keylock option
Enclosure material	Enclosure : self-extinguishing material
Colour	Enclosure : white ( RAL 9003 )

### Environment

Standards	EN 50102 EN 60439-3 IEC 23-3 IEC 60439-3 IEC 60529 IEC 60695-2-1
Fire resistance	Back part : 650 °C ( 30 s ) conforming to IEC 60695-2-1 Front face : 650 °C ( 30 s ) conforming to IEC 60695-2-1
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

Warranty period 18 months

Product Life Status	END-OF-SALE NOTICE
---------------------	--------------------