



### Main

Range	Mini Pragma
Range of product	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	4
Number of horizontal rows	1
Provided equipment	Marking kit ( 1 ) Insulating plug ( 1 ) Terminal block support ( 2 ) Earth-neutral terminal blocks 4 holes ( 2 )
Type of front cover	Transparent
Width	112 mm
Height	200 mm
Depth	94 mm

### Complementary

Enclosure mounting	Surface
9 mm pitches	8
Total number of 18 mm modules	4
[In] rated current	50 A
[Ui] rated insulation voltage	< 690 V
Type of rail	DIN
Number of terminal blocks	2 neutral / earth terminal block with 4 Quick outgoers
Distribution block outgoers	4 x 10 mm <sup>2</sup> for earth / neutral 4 x 16 mm <sup>2</sup> for earth / neutral
Locking options description	Keylock option
Enclosure material	Enclosure : self-extinguishing material
Colour	Enclosure : white ( RAL 9003 )

### Environment

Standards	IEC 60695-2-1 IEC 60439-3 EN 60439-3
-----------	--

EN 50102  
IEC 60529

Fire resistance	Back part : 650 °C conforming to IEC 60695-2-1 Front face : 650 °C conforming to IEC 60695-2-1
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102

### Contractual warranty

Warranty period	18 months
-----------------	-----------