



Main

Range	Mini Pragma
Range of product	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	12
Number of horizontal rows	1
Provided equipment	Marking kit (1) Terminal block support (2) Earth-neutral terminal blocks 4 holes (1) Earth-neutral terminal blocks 8 holes (1)
Type of front cover	Opaque

Complementary

Enclosure mounting	Flush
9 mm pitches	24
Total number of 18 mm modules	12
[In] rated current	63 A
[Ui] rated insulation voltage	< 690 V
Type of rail	DIN
Number of terminal blocks	1 neutral / earth terminal block with 4 Quick outgoers 1 neutral / earth terminal block with 8
Distribution block outgoers	12 x 10 mm ² for earth / neutral 12 x 16 mm ² for earth / neutral
Locking options description	Keylock option
Enclosure material	Enclosure : self-extinguishing material
Colour	Enclosure : white (RAL 9003)

Environment

Standards	IEC 60529 IEC 60695-2-1 IEC 60439-3 EN 60439-3 EN 50102
Fire resistance	Back part : 650 °C conforming to IEC 60695-2-1

Front face : 650 °C conforming to IEC 60695-2-1

IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102

Contractual warranty

Warranty period	18 months
-----------------	-----------
