



Main

| | |
|---------------------------------|---|
| Range | Mini Pragma |
| Range of product | Mini Pragma |
| Product or component type | Enclosure |
| Enclosure type | Modular enclosure |
| Number of 18 mm modules per row | 18 |
| Number of horizontal rows | 1 |
| Provided equipment | Marking kit (1) Terminal block support (2) Earth-neutral terminal blocks 16 holes (2) |
| Type of front cover | Opaque |

Complementary

| | |
|-------------------------------|--|
| Enclosure mounting | Flush |
| 9 mm pitches | 36 |
| Total number of 18 mm modules | 18 |
| [In] rated current | 63 A |
| [Ui] rated insulation voltage | < 690 V |
| Type of rail | DIN |
| Number of terminal blocks | 2 neutral / earth terminal block with 16 Quick outgoing |
| Distribution block outgoing | 16 x 10 mm ² for earth / neutral 16 x 16 mm ² for earth / neutral |
| Locking options description | Keylock option |
| Enclosure material | Enclosure : self-extinguishing material |
| Colour | Enclosure : white (RAL 9003) |

Environment

| | |
|-----------------|---|
| Standards | IEC 60529 IEC 60439-3 EN 50102 IEC 60695-2-1 EN 60439-3 |
| Fire resistance | Back part : 650 °C conforming to IEC 60695-2-1 Front face : 650 °C conforming to IEC 60695-2-1 |

| | |
|-------------------------|------------------------------|
| IP degree of protection | IP40 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to EN 50102 |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
