



### Main

Range	Mini Pragma
Range of product	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	12
Number of horizontal rows	2
Provided equipment	Marking kit ( 1 ) Insulating plug ( 1 ) Terminal block support ( 2 ) Earth-neutral terminal blocks 16 holes ( 2 )
Type of front cover	Opaque
Width	256 mm
Height	326 mm
Depth	96 mm

### Complementary

Enclosure mounting	Surface
9 mm pitches	24
Total number of 18 mm modules	24
[In] rated current	63 A
[Ui] rated insulation voltage	< 690 V
Type of rail	DIN
Number of terminal blocks	2 neutral / earth terminal block with 16 Quick outgoing
Distribution block outgoing	16 x 10 mm <sup>2</sup> for earth / neutral 16 x 16 mm <sup>2</sup> for earth / neutral
Locking options description	Keylock option
Enclosure material	Enclosure : self-extinguishing material
Colour	Enclosure : white ( RAL 9003 )

### Environment

Standards	EN 50102 EN 60439-3 IEC 60439-3
-----------	---------------------------------------

13912

IEC 60529  
IEC 60695-2-1

Fire resistance	Back part : 650 °C conforming to IEC 60695-2-1 Front face : 650 °C conforming to IEC 60695-2-1
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102

### Contractual warranty

Warranty period	18 months
-----------------	-----------