

Product data sheet

Characteristics

13923

Mini Pragma surface enclosure - IP 40 - 3 x 12 modules - transparent door



Main

Range	Mini Pragma
Range of product	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	12
Number of horizontal rows	3
Provided equipment	Marking kit (1) Insulating plug (1) Terminal block support (2) Earth-neutral terminal blocks 22 holes (2)
Type of front cover	Transparent
Width	256 mm
Height	451 mm
Depth	96 mm

Complementary

Enclosure mounting	Surface
9 mm pitches	24
Total number of 18 mm modules	36
[In] rated current	63 A
[Ui] rated insulation voltage	< 690 V
Type of rail	DIN
Number of terminal blocks	2 neutral / earth terminal block with 22 Quick outgoers
Distribution block outgoers	22 x 10 mm ² for earth / neutral 22 x 16 mm ² for earth / neutral
Locking options description	Keylock option
Enclosure material	Enclosure : self-extinguishing material
Colour	Enclosure : white (RAL 9003)

Environment

Standards	EN 60439-3 EN 50102 IEC 60695-2-1
-----------	---

IEC 60529
IEC 60439-3

Fire resistance	Back part : 650 °C conforming to IEC 60695-2-1 Front face : 650 °C conforming to IEC 60695-2-1
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102

Contractual warranty

Warranty period	18 months
-----------------	-----------