

Product data sheet

Characteristics

13958

mini Kaedra - for modular device - 1 openings - 6 modules - 1 terminal block



Main

Range of product	Kaedra
Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Mini enclosure for modular device
Accessories included with enclosure	1 marking kit 1 terminal block 8 holes 1 terminal block support

Complementary

Enclosure mounting	Surface
9 mm pitches	12
Number of 18 mm modules per row	6
Total number of 18 mm modules	6
Number of horizontal rows	1
Electrical insulation class	Class II Double insulation
Provided equipment	1 marking kit 1 terminal block 8 holes 1 terminal block support
Type of front cover	Transparent
Power dissipation in W	11 W
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	3
Number of terminal blocks	1 with 8 outgoers
Distribution block outgoers	4 x 10 mm ² 4 x 16 mm ²
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Width	159 mm
Height	200 mm
Depth	112 mm
Colour	Door : transparent green

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Enclosure : light grey (RAL 7035)

Market segment	Residential Small commercial
Targeted country	France

Environment

Standards	EN 50102 EN 50262 IEC 60439-3 IEC 60529 IEC 670
Fire resistance	750 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------