



### Main

Range of product	Kaedra
Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Mini enclosure for modular device
Accessories included with enclosure	1 marking kit 1 terminal block 16 holes 1 terminal block support

### Complementary

Enclosure mounting	Surface
9 mm pitches	24
Number of 18 mm modules per row	12
Total number of 18 mm modules	12
Number of horizontal rows	1
Electrical insulation class	Class II Double insulation
Provided equipment	1 marking kit 1 terminal block support 1 terminal block 16 holes
Type of front cover	Transparent
Power dissipation in W	19 W
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	7
Number of terminal blocks	1 with 16 outgoers
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Width	267 mm
Height	200 mm
Depth	112 mm
Colour	Door : transparent green Enclosure : light grey ( RAL 7035 )
Market segment	Residential

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Small commercial

Targeted country

France

## Environment

Standards

EN 50102  
IEC 60529  
IEC 670  
EN 50262  
IEC 60439-3

Fire resistance

750 °C conforming to IEC 60695-2-1

IP degree of protection

IP65 conforming to IEC 60529

IK degree of protection

IK09 conforming to EN 50102

Environmental characteristic

UV resistant class 3 conforming to ISO 4582 2010  
Ultraviolet degradation test conforming to ISO 4892-2 2013

Overvoltage category

II

Ambient air temperature for operation

-25...60 °C

## Contractual warranty

Warranty period

18 months