



Main

Range of product	Kaedra
Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for modular device
Accessories included with enclosure	1 terminal block 8 holes 1 wiring strap 1 terminal block support 1 marking kit

Complementary

Enclosure mounting	Surface
9 mm pitches	24
Number of 18 mm modules per row	12
Total number of 18 mm modules	12
Number of horizontal rows	1
Electrical insulation class	Double insulation Class II
Provided equipment	1 marking kit 1 wiring strap 1 terminal block 8 holes 1 terminal block support
Type of front cover	Reversible Transparent
Power dissipation in W	24 W
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	17
Number of terminal blocks	1 with 8 outgoers
Distribution block outgoers	4 x 10 mm ² 4 x 16 mm ²
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Width	340 mm
Height	280 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Depth	160 mm
Colour	Door : transparent green Enclosure : light grey (RAL 7035)
Market segment	Small commercial Residential
Targeted country	France

Environment

Standards	EN 50262 IEC 60529 EN 50102 IEC 670 IEC 60439-3
Fire resistance	750 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------