



### Main

Range of product	Kaedra
Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for modular device
Accessories included with enclosure	1 terminal block support 2 marking kits 1 terminal block 22 holes 2 wiring straps

### Complementary

Enclosure mounting	Surface
9 mm pitches	24
Number of 18 mm modules per row	12
Total number of 18 mm modules	24
Number of horizontal rows	2
Electrical insulation class	Class II Double insulation
Provided equipment	2 marking kit 2 wiring strap 1 terminal block support 1 terminal block 22 holes
Type of front cover	Transparent Reversible
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	17
Number of terminal blocks	1 with 22 outgoing
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Width	340 mm
Height	460 mm
Depth	160 mm
Colour	Door : transparent green Enclosure : light grey ( RAL 7035 )

Market segment	Residential Small commercial
Targeted country	France

## Environment

Standards	EN 50262 IEC 60439-3 IEC 670 IEC 60529 EN 50102
Fire resistance	750 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

## Contractual warranty

Warranty period	18 months
-----------------	-----------