

Product data sheet

Characteristics

13965

Kaedra - for modular device - 2 x 18 modules - 1 terminal block



Main

Range of product	Kaedra
Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for modular device
Accessories included with enclosure	2 wiring straps 1 terminal block support 1 terminal block 32 holes 2 marking kits

Complementary

Enclosure mounting	Surface
9 mm pitches	36
Number of 18 mm modules per row	18
Total number of 18 mm modules	36
Number of horizontal rows	2
Electrical insulation class	Double insulation Class II
Provided equipment	2 marking kit 2 wiring strap 1 terminal block support 1 terminal block 32 holes
Type of front cover	Transparent Reversible
[In] rated current	90 A
Type of rail	DIN
Number of pre-cutouts PG ISO	17
Number of terminal blocks	1 with 32 outgoing
Distribution block outgoing	16 x 10 mm ² 16 x 16 mm ²
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Width	448 mm
Height	460 mm
Depth	160 mm

Colour	Door : transparent green Enclosure : light grey (RAL 7035)
Market segment	Small commercial Residential
Targeted country	France

Environment

Standards	IEC 60529 IEC 60439-3 IEC 670 EN 50262 EN 50102
Fire resistance	750 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------