

Product data sheet

Characteristics

13967

Kaedra - for modular device - 3 x 18 modules - 2 terminal blocks



Main

Range of product	Kaedra
Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for modular device
Accessories included with enclosure	2 terminal block 22 holes 2 terminal block supports 3 marking kits 3 wiring straps

Complementary

Enclosure mounting	Surface
9 mm pitches	36
Number of 18 mm modules per row	18
Total number of 18 mm modules	54
Number of horizontal rows	3
Electrical insulation class	Class II Double insulation
Provided equipment	3 marking kit 3 wiring strap 2 terminal block 22 holes 2 terminal block support
Type of front cover	Reversible Transparent
Power dissipation in W	65 W
[In] rated current	125 A
Type of rail	DIN
Number of pre-cutouts PG ISO	17
Number of terminal blocks	2 with 22 outgoers
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Width	448 mm
Height	610 mm
Depth	160 mm
Colour	Door : transparent green

Enclosure : light grey (RAL 7035)

Market segment	Residential Small commercial
Targeted country	France

Environment

Standards	EN 50102 EN 50262 IEC 60439-3 IEC 60529 IEC 670
Fire resistance	750 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------