



Main

Range of product	Kaedra
Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for modular device with interface
Accessories included with enclosure	1 plate for 65 x 85 power outlets 1 terminal block 22 holes 1 terminal block support 2 marking kits 2 wiring straps 3 plates for push-button controls

Complementary

Enclosure mounting	Surface
9 mm pitches	24
Number of 18 mm modules per row	12
Total number of 18 mm modules	24
Number of horizontal rows	2
Electrical insulation class	Class II Double insulation
Number of openings of interface	3
Number of plates	3 for push-button controls 1 for 65 x 85 power outlets
Provided equipment	2 marking kit 2 wiring strap 1 plate for 65 x 85 power outlet 3 plate for push-button control 1 terminal block support 1 terminal block 22 holes
Type of front cover	Reversible Transparent
[In] rated current	90 A
Type of rail	DIN
Number of pre-cutouts PG ISO	17
Number of terminal blocks	1 with 22 outgoers
Locking options description	Optional keylock

Enclosure material	Self-extinguishing polymer
Base dimension	90 x 100 mm
Width	448 mm
Height	460 mm
Depth	160 mm
Colour	Door : transparent green Enclosure : light grey (RAL 7035)
Market segment	Residential Small commercial
Targeted country	France

Environment

Standards	EN 50102 EN 50262 IEC 60439-3 IEC 60529 IEC 670
Fire resistance	750 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------