



Main

Range of product	Kaedra
Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Interface enclosure
Accessories included with enclosure	1 plate for 65 x 85 power outlets 4 plates for push-button controls

Complementary

Enclosure mounting	Surface
Electrical insulation class	Double insulation Class II
Number of openings of interface	4
Number of plates	4 for push-button controls 1 for 65 x 85 power outlets
Provided equipment	1 plate for 65 x 85 power outlet 4 plate for push-button control
Type of front cover	Opaque
[In] rated current	63 A
Number of pre-cutouts PG ISO	3
Enclosure material	Self-extinguishing polymer
Base dimension	90 x 100 mm
Width	138 mm
Height	610 mm
Depth	160 mm
Colour	Enclosure : light grey (RAL 7035)
Market segment	Residential Small commercial
Targeted country	France

Environment

Standards	EN 50102 IEC 670 IEC 60439-3
-----------	------------------------------------

IEC 60529
EN 50262

Fire resistance	750 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------