

Product data sheet

Characteristics

13983

Kaedra - for modular device - 2 x 12 modules - 1+1 terminal blocks



Main

Range of product	Kaedra
Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for modular device
Accessories included with enclosure	2 marking kits 1 terminal block 4 holes 1 terminal block 22 holes 2 wiring straps 1 terminal block support

Complementary

Enclosure mounting	Surface
9 mm pitches	24
Number of 18 mm modules per row	12
Total number of 18 mm modules	24
Number of horizontal rows	2
Electrical insulation class	Double insulation Class II
Provided equipment	2 marking kit 2 wiring strap 1 terminal block 4 holes 1 terminal block support 1 terminal block 22 holes
Type of front cover	Transparent Reversible
Power dissipation in W	34 W
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	17
Number of terminal blocks	1 with 22 outgoing 1 with 4 outgoing
Distribution block outgoing	13 x 10 mm ² 13 x 16 mm ²
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer

Width	340 mm
Height	460 mm
Depth	160 mm
Colour	Door : transparent green Enclosure : light grey (RAL 7035)
Market segment	Residential Small commercial
Targeted country	Spain

Environment

Standards	EN 50102 IEC 60529 IEC 60439-3 IEC 60695-2-1 IEC 670 EN 50262
Fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------