



Main

Range of product	Modicon Quantum automation platform
Product or component type	Unity processor

Complementary

Mode of transmission	Single mode
Clock frequency	266 MHz
Number of slots	4 10 2 6 16
Number of racks	2 - local rack(s)
Number of distributed I/O station	63 station(s) - 1 rack(s) - 3 Modbus Plus network(s)
Number of remote I/O station	31 - 2 S908 remote I/O rack(s) 31 - 2 ethernet Quantum remote I/O rack(s) 31 - 2 ethernet X80 remote I/O rack(s)
Discrete I/O number	Unlimited (31 drops of 28 slots max) - ethernet remote I/O 0 - local - forbidden in Hot Standby application 8000 inputs, 8000 outputs - distributed - per network Modbus Plus 31744 inputs, 31744 outputs - remote
Analogue I/O number	Unlimited (31 drops of 28 slots max) - ethernet remote I/O 0 - local - forbidden in Hot Standby application 500 inputs, 500 outputs - distributed - per network Modbus Plus 1984 inputs, 1984 outputs - remote
Application specific I/O	Accurate time stamping Counter Serial link High-speed interrupt inputs
Communication service	Ethernet router
Number of optional modules	6 (Ethernet, Modbus, Modbus Plus, Profibus DP, Sy/Max)
Maximum number of connections	1 (USB) 2 (AS-Interface) - distributed 4 (AS-Interface) - remote

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	6 (Ethernet TCP/IP) - local 6 (Modbus Plus) - local 6 (Profibus DP) - local 1 (Modbus) - RS232/485 Modbus/ASCII
Integrated connection type	1 Modbus Plus with 1 Modbus with 1 USB with 1 optic fibre with Hot Standby protocol
Checks	Hot standby Process control
Memory description	Internal RAM 11264 kB - 1536 kB for data Expandable 8 MB - file storage with PCMCIA card
Switch function	Key switch memory port on/off
Application structure	1 cyclic/periodic master task - 1 periodic fast task - forbidden in Hot Standby application 128 I/O interrupt tasks - forbidden in Hot Standby application 128 interrupt tasks - forbidden in Hot Standby application 32 timer interrupt tasks - forbidden in Hot Standby application 4 auxiliary tasks - forbidden in Hot Standby application
Number of instructions per ms	10.28 Kinst/ms if 100 % Boolean 10.07 Kinst/ms if 65 % Boolean and 35 % numerical
System overhead	1 ms - master task 0.2 ms - fast task
Bus current requirement	2760 mA
Local signalling	1 LED green for Ethernet activity (COM) 1 LED red for Ethernet collision
Electrical connection	1 connector, connector type: RJ45 for connecting Modbus bus 1 female connector, connector type: SUB-D 9 for connecting to the Modbus Plus network 1 connector, connector type: LC (single mode fiber optic) for interconnecting primary and secondary PLCs up to 16 km

Environment


Protective treatment	Conformal coating Humiseal 1A33
Product certifications	Misc (Marine) GOST UL CE CSA
Standards	HazLoc

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1625 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Racks for Modules Mounting

Dimensions of Modules and Racks



- (1) 2 slots
- (2) 3 slots
- (3) 4 slots
- (4) 6 slots
- (5) 10 slots
- (6) 16 slots