Product data sheet Characteristics

14883

comb busbar - 3 poles - 80 A - L = 12 x 18 mm



Main		
Range of product	C60 IC60 IK60	
	STI	
Product or component type	Comb busbar	
Accessory / separate part category	Connection accessory	
Poles description	3P	
Distance between way	54 mm	
Marking	L1 L2 L3	
Connector type	Tooth	
Total number of 18 mm modules	12	
Complementary		
[In] rated current	Double feed 100 A (40 °C) Single feed 80 A (40 °C)	
[Ui] rated insulation voltage	500 V conforming to IEC 664	
Mounting mode	Horizontal	
9 mm pitches	24	
Product compatibility	C60 IC60 STI IK60	
Compatibility code	CombBusbar_C60	
Offer Sustainability		
Product environmental profile	Available Product environmental	
Product end of life instructions	Need no specific recycling operations	
Contractual warranty	4.4000	
Warranty period	18 months	
Mar 42, 2040		

Complementary

[In] rated current	Double feed 100 A (40 °C) Single feed 80 A (40 °C)
[Ui] rated insulation voltage	500 V conforming to IEC 664
Mounting mode	Horizontal
9 mm pitches	24
Product compatibility	C60 IC60 STI IK60
Compatibility code	CombBusbar_C60

Offer Sustainability

Product environmental profile	Available Product environmental	i.
Product end of life instructions	Need no specific recycling operations	<u>.</u>

Contractual warranty

Warranty period	18 months