



Main

Range of product	Acti 9
Range	Acti 9
Product name	Acti 9 iCM
Product or component type	Selector switch
Device short name	ICMA
Device application	Ammeter selector
[Ue] rated operational voltage	< 440 V AC 50/60 Hz

Complementary

[I _{th}] conventional free air thermal current	10 A
[I _e] rated operational current	10 A
Control type	Rotary handle 4 positions
Marking	0 - L1 - L2 - L3
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	4
Height	60 mm
Width	36 mm
Depth	75 mm
Mechanical durability	2000000 cycles
Electrical durability	1000000 cycles
Connections - terminals	Captive screw-jumper terminals
Market segment	Residential Small commercial
Compatibility code	CMA

Environment

Standards	IEC 60947-3
IP degree of protection	IP66 front face IP20 terminals
Ambient air temperature for operation	-20...55 °C

Ambient air temperature for storage	-25...80 °C
-------------------------------------	-------------

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0705 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------
