



### Main

|                           |                                |
|---------------------------|--------------------------------|
| Range                     | Acti 9                         |
| Range of product          | Acti 9                         |
| Product name              | Acti 9 iAMP                    |
| Device short name         | IAMP                           |
| Product or component type | Ammeter                        |
| Range compatibility       | Prisma G door<br>Prisma P door |
| Network type              | AC 50/60 Hz                    |
| Mounting support          | DIN rail                       |

### Complementary

|                           |   |
|---------------------------|---|
| Type of measurement       | Current   |
| [Us] rated supply voltage | 230 AC 50/60 Hz                                     |
| Power consumption in VA   | 0.3 VA  |
| Power consumption in VA   | 0.3 VA  |
| 9 mm pitches              | 4   |
| Width                     | 36 mm   |
| Height                    | 87 mm   |
| Depth                     | 65 mm   |
| Connections - terminals   | Tunnel type terminal 2 cable(s) 2.5 mm <sup>2</sup> |
| Market segment            | Small commercial<br>Residential                     |
| Compatibility code        | AMP   |

### Environment

|                                       |   |
|---------------------------------------|---|
| Standards                             | EN 50082-1<br>IEC 61010-1<br>EN 50081-1 |
| Ambient air temperature for operation | -20...50 °C                             |

### Offer Sustainability

|                        |   |
|------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 0548 - Schneider Electric declaration of conformity |
|------------------------|---|

 Schneider Electric declaration of conformity

---

REACH

Reference not containing SVHC above the threshold  
Reference not containing SVHC above the threshold

---

**Contractual warranty**

---

Warranty period

18 months

---