



Main

Range of product	Acti 9
Device short name	ITM 4C-6E
Product or component type	Multifunctional time switch
Number of channels	4
Battery type	Lithium
Function available	Automatic time changeover Pulse programming

Complementary

Device application	Building
Measurement accuracy	+/- 1 s/day
Cycle duration	Free yearly programming
Minimum interval duration	1 s
Measurement accuracy	+/- 1 s/day 20 °C
Power consumption in VA	4.5 VA
Maximum switching current	10 A - 250 V AC pf = 1 6 A - 250 V AC pf = 0.6
[Ue] rated operational voltage	230 V (+/- 10 %) AC 50 Hz
Battery life	10 yr
Backup time	5 years time and program saving
Maximum number of switchings	15 time brackets in annual time programming 20 different pulses in pulse programming 45 time brackets in weekly time programming
Provided equipment	Memory key
Mounting support	DIN rail
Number of inputs	6
9 mm pitches	10
Colour	Grey
Function	Pulse programming
Absence for holidays	No
Time changeover	Automatic
Updated by	None

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Compatibility code	ITM_4C-6E
--------------------	-----------

Environment

Ambient air temperature for operation	-5...50 °C
IP degree of protection	IP20 B

Contractual warranty

Warranty period	18 months
-----------------	-----------

Not classified OPS characteristics

Market segment	Residential Small commercial
----------------	---------------------------------
