



Main

Range of product	Acti 9
Range	Acti 9
Product name	Acti 9 IH
Device short name	IH
Product or component type	Mechanical time switch
Number of channels	1
Function available	Manual time changeover

Complementary

Device application	Building
Load type	10 parallel-corrected fluorescent tube, (58 W) 15 parallel-corrected fluorescent tube, (40 W) 230 V AC halogen lamp, (1000 W) 230 V AC incandescent lamp, (1000 W) 3 parallel-corrected fluorescent tube, (100 W) 7 fluocompact lamp, (11 W) 7 fluocompact lamp, (15 W) 7 fluocompact lamp, (20 W) 7 fluocompact lamp, (7 W)
Cycle duration	24 h
Measurement accuracy	+/- 1 s/day
Maximum number of switchings	48 on - 48 off
Minimum interval duration	15 min
Type of setting	Manual time changeover
Measurement accuracy	+/- 1 s/day 20 °C
Power consumption in VA	2.5 VA
Maximum switching current	16 A - 250 V AC pf = 1 4 A - 250 V AC pf = 0.6
[Ue] rated operational voltage	(+/- 10 %) 230 V AC 50/60 Hz
Mounting support	DIN rail

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

9 mm pitches	2
Colour tint	White (RAL 9003)
Connections - terminals	Screw terminals
IP degree of protection	IP20 B
Width	18 mm
Height	90 mm
Depth	66 mm
Product weight	0.097 kg
Function	None
Absence for holidays	No
Time changeover	Manual
Updated by	None
Compatibility code	IH
Market segment	Residential Small commercial

Environment

Ambient air temperature for operation	-10...50 °C
IP degree of protection	Terminals : IP20 B

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0625 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference contains SVHC above the threshold - Go to CaP for more details Go to CaP for more details
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------