



Main

Range of product	Acti 9
Range	Acti 9
Product name	Acti 9 IH
Device short name	IH
Product or component type	Mechanical time switch
Number of channels	2
Function available	Manual time changeover

Complementary

Device application	Building
Load type	1 parallel-corrected fluorescent tube, balast : conventional, (58 W) 10 non-corrected fluorescent tube, balast : conventional, (58 W) 10 serial-corrected fluorescent tube, balast : conventional, (58 W) 15 non-corrected fluorescent tube, balast : conventional, (40 W) 15 serial-corrected fluorescent tube, balast : conventional, (40 W) 2 parallel-corrected fluorescent tube, balast : conventional, (40 W) 230 V AC halogen lamp, (1100 W) 230 V AC incandescent lamp, (1100 W) 3 dual mounted fluorescent tube, balast : conventional, (2 x 100 W) 5 dual mounted fluorescent tube, balast : conventional, (2 x 58 W) 6 non-corrected fluorescent tube, balast : conventional, (100 W) 6 serial-corrected fluorescent tube, balast : conventional, (100 W)
Cycle duration	24 h
Measurement accuracy	+/- 1 s/day
Maximum number of switchings	24 on - 24 off
Minimum interval duration	30 min
Type of setting	Manual time changeover
Measurement accuracy	+/- 1 s/day 20 °C
Power consumption in VA	2.5 VA
Maximum switching current	16 A - 250 V AC pf = 1 4 A - 250 V AC pf = 0.6
[Ue] rated operational voltage	(- 15...10 %) 230 V AC 50/60 Hz
Battery life	6 yr
Backup time	150 h time and program saving
Mounting support	DIN rail

9 mm pitches	6
Colour tint	White (RAL 9003)
Connections - terminals	Screw terminals
IP degree of protection	IP20 B
Width	54 mm
Height	82 mm
Depth	66 mm
Product weight	0.216 kg
Function	None
Absence for holidays	No
Time changeover	Manual
Updated by	None
Compatibility code	IH
Market segment	Small commercial Residential

Environment

Ambient air temperature for operation	-20...55 °C
IP degree of protection	Terminals : IP20 B

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0619 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference contains SVHC above the threshold - Go to CaP for more details Go to CaP for more details

Contractual warranty

Warranty period	18 months
-----------------	-----------