



Main

Range of product	Easy9 Domae
Range	Easy9
Product name	Easy9 CT
Product or component type	Contacteur
Device short name	CT
Device application	Control circuit
Poles description	2P
Pole contact composition	2 NO
Network type	AC
Control type	Remote control
[Uc] control circuit voltage	230 V AC 50 Hz

Complementary

[Ie] rated operational current	20 A AC-7A
Network frequency	50/60 Hz
[Ue] rated operational voltage	250 V AC 50 Hz
Maximum power	2.1 W 250 V AC
[Ui] rated insulation voltage	500 V AC 50 Hz
Control signal type	Maintained
Local signalling	Mechanical color indicator
Hold-in power consumption in VA	2.7 VA
Inrush power in VA	9.2 VA
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	60 mm

Product weight	120 g
Colour	Grey
Electrical durability	200000 cycles AC 50/60 Hz conforming to EN 61095
Connections - terminals	Power circuit : 2 tunnel type terminals 2.5 mm ² for flexible cable(s) Power circuit : 1 tunnel type terminals 6 mm ² for rigid cable(s) Control circuit : 2 tunnel type terminals 2.5 mm ² for flexible cable(s) Control circuit : 2 tunnel type terminals 1.5 mm ² for rigid cable(s)
Product compatibility	Time delay Interference filter Auxiliary contact Mixed control: impulse/latched
Compatibility code	CT

Environment

Standards	IEC 61095 EN 61095
Product certifications	IMQ VDE EAC
Noise level	30 dB
IP degree of protection	IP40 (in modular enclosure) conforming to IEC 60529 IP20 conforming to IEC 60529
Pollution degree	2
Operating altitude	2000 m
Ambient air temperature for operation	-5...60 °C
Ambient air temperature for storage	-40...60 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------