



Main

Range of product	TL
Product or component type	Extension for impulse relay
Device short name	ETL
Relay application	Remote control
Poles description	1P
Pole contact composition	1 NO
[In] rated current	32 A
Network type	AC

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	250 V AC 50/60 Hz
Control type	Toggle Remote control
Control signal type	Impulse
Switching frequency	5 switching operations/minute
Impulse duration	50 ms
Remote control type	Illuminated push-button
Local signalling	ON/OFF indication
[Uc] control circuit voltage	110 V DC 230...240 V AC 50/60 Hz
Supply inrush power	19 VA
Mounting mode	Fixed, on right side of TL
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	84 mm
Width	18 mm
Depth	60 mm
Colour	Grey
Electrical durability	AC-21 : 50000 cycles AC-22 : 20000 cycles
Connections - terminals	Tunnel type terminals

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Auxiliary connection terminal	Control circuit : tunnel type terminals 0.5...6 mm ²
Compatibility code	ETL

Environment

Noise level	<= 60 dB
Tropicalisation	2
Relative humidity	95 % (55 °C)
Ambient air temperature for operation	-20...50 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------