



Main

| | |
|------------------------------|-----------------------------|
| Range of product | TL |
| Product or component type | Impulse relay |
| Device short name | TL |
| Device application | Remote control |
| Poles description | 1P |
| Pole contact composition | 1 NO |
| [In] rated current | 16 A |
| Network type | AC |
| [Uc] control circuit voltage | 12 V DC 24 V AC 50/60 Hz |

Complementary

| | |
|--------------------------------|---|
| Network frequency | 50/60 Hz |
| [Ue] rated operational voltage | 250 V AC 50/60 Hz |
| Control type | Coil deconnection Remote control |
| Control signal type | Impulse |
| Switching frequency | 100 switching operations/day 5 switching operations/minute |
| Impulse duration | 50 ms...1 s |
| Remote control type | Illuminated push-button 3 mA |
| Local signalling | ON/OFF indication |
| Mounting mode | Fixed |
| Mounting support | DIN rail |
| 9 mm pitches | 2 |
| Height | 84 mm |
| Width | 18 mm |
| Depth | 60 mm |
| Electrical durability | AC-22 : 100000 cycles AC-21 : 200000 cycles |
| Range compatibility | Multi 9 ATet Multi 9 ATL |
| Compatibility code | TL |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

| | |
|---------------------------------------|---------------------------|
| Standards | EN 669-1 EN 669-2-2 |
| Product certifications | GOST |
| Quality labels | NF IMQ VDE CEBEC |
| Noise level | 60 dB |
| Tropicalisation | 2 |
| Relative humidity | 95 % (55 °C) |
| Ambient air temperature for operation | -20...50 °C |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|