



Main

Range of product	Acti 9
Range	Acti 9
Product name	Acti 9 THP
Device short name	THP2
Product or component type	Programmable thermostat
Colour tint	White RAL 9003
Provided equipment	Supplied with two non-adjustable ambient temperature probes

Complementary

Power consumption in VA	1 VA
Maximum switching current	1 A - 250 V pf = 0.6 5 A - 250 V pf = 1
[Ue] rated operational voltage	230 V AC
Number of zones	2
Control type	Push-button Remote contact
Operating mode	Above freezing : 6 °C Comfort : 5...30 °C Reduced : 5...26 °C
Cycle duration	7 days 24 hours
Measurement accuracy	+/- 0.2 °C
Information displayed	Hour Day Minutes
Display type	LCD
Status LED	2, green indicator light : above freezing operating mode 2, red indicator light : make position of the output contacts 2, yellow indicator light : automatic operating mode 2, yellow indicator light : comfort operating mode 2, yellow indicator light : reduced operating mode

Maximum number of switchings	168
Minimum interval duration	1 min
Backup time	6 years time and program saving
Mounting support	DIN rail
9 mm pitches	10
Function available	Manual time changeover
Connections - terminals	Screw terminals
Height	81 mm
Width	90 mm
Depth	65 mm
Compatibility code	THP2

Environment

IP degree of protection	IP20
-------------------------	------

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0952 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------